

Search within category

GO

BUY NOW

DESIGN / INSTALL



ILT2S-C

Belt-Ty™ in-line locking tie, standard cross section, 8.3" (211mm) length, nylon 6.6, natural, standard package.

Specs

Packaging Details

Tools

Documents

★ Add to Favorites

🛒 Add to BOM

Material	Nylon 6.6
Application	General
Color	Natural
Environment	Plenum
Cross Section	Standard
Length (In.)	8.3
Length (mm)	211
Locking Style	Locking
Width (In.)	0.190
Width (mm)	4.8
Plenum-Rated	Yes, AH-2
Tool	GTS-E, GS2B, GTH-E, GS4H, PTS, PTH, PPTS, STS2, STH2
Width In (mm)	0.190 (4.8)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	MS3367-23-9
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes

ILT2S-C Cable Tie, In-Line, 8.3"L (211mm), Standard, Nylon, Natural Panduit	
UL Recognized (File #E56854)	Yes
Installation Temperature	-4°F (-20°C) - 32°F (0°C)
Max. Bundle Diameter (mm)	48
Min. Loop Tensile Strength (N)	222
Operating Temperature	-76°F (-60°C) - 185°F (85°C)
Part Features	Parallel-entry cable tie that threads like a belt (180° entry), Low profile head avoids snags and reduces overall bundle size, 35% lower head height than conventional 90° ties
Style	In-Line (Belt)
Type	In-Line/Low Profile Ties
RoHS Compliancy Status	Compliant
Min. Order Qty.	100.0000

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)