



Search Panduit.com



Search within category

BUY NOW

DESIGN / INSTALL



PLT.6SM-M

Pan-Ty® locking tie, subminiature cross section, 2.8" (71mm) length, nylon 6.6, natural, bulk package.

Specs	Tools	Documents	★ Add to Favorites	🛒 Add to BOM
Std. Pkg. Qty.	1000			
Material	Nylon 6.6			
Color	Natural			
Cross Section	Subminiature			
Locking Style	Locking			
Min. Loop Tensile Strength Lbs. (N)	8 (36)			
Continuous Use Temperature Range	-76° (-60°) - 185° (85°)			
Plenum-Rated	No			
Tool	GTS, GTSL, PTS			
Length In (mm)	2.8 (71)			
Thickness In (mm)	0.030 (0.8)			
Bundle Diameter Range In. (mm)	0.01 (0.3) - 0.60 (15)			
CE Compliant	Yes			
CSA Certified	Yes			
Mil. Std. Part Number	—			
UL 62275 Compliant (Type 1, 11)	Yes			
UL 62275 Compliant (Type 2, 21)	—			
UL Listed (File #E56854)	No			
UL Recognized (File #E56854)	Yes			
Application	General			
Environment	Indoor			
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.			
UV Resistant	No			
Width In (mm)	0.07 (1.8)			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1,000.0000			