



Search within category

GO

BUY NOW

DESIGN / INSTALL



PLT1.5M-C

Pan-Ty® locking tie, miniature cross section, 5.6" (142mm) length, nylon 6.6, natural, standard package.

Specs

Tools

Documents

★ Add to Favorites

🛒 Add to BOM

Std. Pkg. Qty.	100
Material	Nylon 6.6
Color	Natural
Cross Section	Miniature
Locking Style	Locking
Min. Loop Tensile Strength Lbs. (N)	18 (80)
Plenum-Rated	Yes, AH-2
Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
Length In (mm)	5.6 (142)
Thickness In (mm)	0.043 (1.1)
Bundle Diameter Range In. (mm)	0.06 (1.5) - 1.25 (32)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	—
UL 62275 Compliant (Type 1, 11)	—
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Application	General
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Environment	Plenum
Installation Temperature	-20°C - 0°C
Operating Temperature	-60°C - 85°C
Part Features	One piece construction provides consistent, reliable performance. Low thread force.
Releasable	No
Thickness (mm)	1.1
Width In (mm)	0.098 (2.5)
RoHS Compliancy Status	Compliant

Min. Order Qty.

100.0000