

Search within categoryGO

BUY NOW

DESIGN / INSTALL



PLT1.5M-M0

Pan-Ty® locking tie, miniature cross section, 5.6" (142mm) length, weather resistant nylon 6.6, black, bulk package.

SpecsPackaging DetailsToolsDocuments★ Add to Favorites🛒 Add to BOM

Product Type	Cable Ties
Material	Weather Resistant Nylon 6.6
Color	Black
Cross Section	Miniature
Locking Style	Locking
Min. Loop Tensile Strength Lbs. (N)	18 (80)
Plenum-Rated	No
Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
Length In (mm)	5.6 (142)
Thickness In (mm)	0.043 (1.1)
Bundle Diameter Range In. (mm)	0.06 (1.5) - 1.25 (32)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	—
UL 62275 Compliant (Type 1, 11)	—
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Application	General
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Environment	Plenum
Installation Temperature	-4°F (-20°C) - 32°F (0°C)
Min. Loop Tensile Strength (N)	80
Operating Temperature	-76°F (-60°C) - 185°F (85°C)
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
Releasable	false

Width In (mm) 0.098 (2.5)

[Back to Top](#)



RoHS Compliancy Status Compliant

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)

Min. Order Qty. 1,000.0000