



Search within category

BUY NOW

DESIGN / INSTALL



PLT1M-M0

Pan-Ty® locking tie, miniature cross section, 3.9" (99mm) length, weather resistant nylon 6.6, black, bulk package.

- Specs
- Packaging Details
- Tools
- Documents
- ★ Add to Favorites
- 🛒 Add to BOM

Material	Weather Resistant Nylon 6.6
Color	Black
Cross Section	Miniature
Locking Style	Locking
Min. Loop Tensile Strength Lbs. (N)	18 (80)
Plenum-Rated	No
Tool	GTS-E, GS2B, PTS, PPTS, STS2
Length In (mm)	3.9 (99)
Thickness In (mm)	0.043 (1.1)
Bundle Diameter Range In. (mm)	0.06 (1.5) - 0.87 (22)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	—
UL 62275 Compliant (Type 1, 11)	No
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Application	General

PLT1M-M0 Cable Tie, 3.9"L (99mm), Miniature, Weather Resistant, Black Panduit	
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Environment	Outdoor (UV Resistant)
Installation Temperature	-4°F (-20°C) - 32°F (0°C)
Min. Loop Tensile Strength (N)	80
Operating Temperature	-76°F (-60°C) - 185°F (85°C)
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
Width In (mm)	0.098 (2.5)
RoHS Compliancy Status	Compliant
Min. Order Qty.	1,000.0000

[Back to Top](#)