



Search within category

GO

BUY NOW

DESIGN / INSTALL



PLT2I-C

Pan-Ty® locking tie, intermediate cross section, 8.0" (203mm) length, nylon 6.6, natural, standard package.

Specs

Tools

Documents

★ Add to Favorites

🛒 Add to BOM

RoHS Compliance Status	Compliant
Material	Nylon 6.6
Color	Natural
CSA Certified	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Mil. Std. Part Number	—
Width (In.)	0.142
Length (In.)	8.0
Length (mm)	203
Width (mm)	3.6
Max. Continuous Use Temperature	185°F (85°C)
CE Compliant	Yes
Locking Style	Locking
Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
Thickness (mm)	1.1
UL 62275 Compliant (Type 2, 21)	Yes
Min. Loop Tensile Strength (N)	178
Min. Loop Tensile Strength (Lbs.)	40
Min. Bundle Diameter (mm)	1.5
Min. Bundle Diameter (In.)	0.06
Max. Bundle Diameter (mm)	51
Max. Bundle Diameter (In.)	2.00
Cross Section	Intermediate
Thickness (In.)	0.045
Plenum-Rated	Yes, for use in plenum or air handling spaces per NEC Sec. 300.22 (C) and (D)
Min. Order Qty.	100.0000

