



SOLUTIONS

PRODUCTS AND SERVICES

SUPPORT

ABOUT US

Search Panduit.com

GO



Search within category

GO

BUY NOW

DESIGN / INSTALL



PLT2M-M0

Pan-Ty® locking tie, miniature cross section, 8.0" (203mm) length, weather resistant nylon 6.6, black, bulk package.

Specs

Packaging Details

Tools

Documents

★ Add to Favorites

🛒 Add to BOM

Material Weather Resistant Nylon 6.6

Color Black

Cross Section Miniature

Locking Style Locking

Min. Loop Tensile Strength Lbs. (N) 18 (80)

Plenum-Rated No

Tool GTS-E, GS2B, PTS, PPTS, STS2

Length In (mm) 8.0 (203)

Thickness In (mm) 0.043 (1.1)

Bundle Diameter Range In. (mm) 0.06 (1.5) - 2.00 (51)

CE Compliant Yes

CSA Certified Yes

Mil. Std. Part Number —

UL 62275 Compliant (Type 1, 11) No

UL 62275 Compliant (Type 2, 21) Yes

UL Listed (File #E56854) Yes

UL Recognized (File #E56854) Yes

Application General

Continuous Use Temperature Range -76°F (-60°C) - 185°F (85°C)

Environment Outdoor (UV Resistant)

Installation Temperature -4°F (-20°C) - 32°F (0°C)

Min. Loop Tensile Strength (N) 80

Operating Temperature -76°F (-60°C) - 185°F (85°C)

Part Features One-piece locking wedge for cable and high loop tensile strength

Width In (mm) 0.098 (2.5)

RoHS Compliancy Status Compliant

Request a Quote
Are you looking for a free quote on Panduit
Products and Solutions?

Yes, I need a quote!

Request a Quote

Are you looking for a free quote on Panduit Products and Solutions?

Yes, I need a quote! ▶