



Search within category

GO

BUY NOW

DESIGN / INSTALL



PLT2M-M30

Pan-Ty® locking tie, miniature cross section, 8.0" (203mm) length, heat stabilized nylon 6.6, black.

Specs

Tools

Documents

★ Add to Favorites

🛒 Add to BOM

RoHS Compliancy Status	Compliant
Material	Heat Stabilized Nylon 6.6
Color	Black
UL Recognized (File #E56854)	Yes
UL Listed (File #E56854)	Yes
CSA Certified	Yes
Width (In.)	0.098
Width (mm)	2.5
Length (mm)	203
Length (In.)	8.0
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
CE Compliant	Yes
Max. Continuous Use Temperature	239°F (115°C)
Locking Style	Locking
Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2
Thickness (mm)	1.1
UL 62275 Compliant (Type 2, 21)	Yes
Min. Loop Tensile Strength (N)	80
Min. Loop Tensile Strength (Lbs.)	18
Min. Bundle Diameter (mm)	1.5
Min. Bundle Diameter (In.)	0.06
Max. Bundle Diameter (mm)	51
Max. Bundle Diameter (In.)	2.00
Cross Section	Miniature
Thickness (In.)	0.043
Plenum-Rated	No
Min. Order Qty.	1,000.0000

