

Search within category

BUY NOW

DESIGN / INSTALL



PLT2S-M

Pan-Ty® locking tie, standard cross section, 7.4" (188mm) length, nylon 6.6, natural, bulk package.

Specs	Tools	Documents	★ Add to Favorites	🛒 Add to BOM
Material	Nylon 6.6			
Application	General			
Color	Natural			
Cross Section	Standard			
Length (In.)	7.4			
Length (mm)	188			
Locking Style	Locking			
Width (In.)	0.190			
Width (mm)	4.8			
Min. Loop Tensile Strength Lbs. (N)	50 (222)			
Plenum-Rated	Yes, AH-2			
Tool	GTS, GTSL, GS2B, GTH, GS4H, PTS, PTH, PPTS, STS2, STH2			
Length In (mm)	7.4 (188)			
Thickness In (mm)	0.052 (1.3)			
Bundle Diameter Range In. (mm)	0.06 (1.5) - 1.88 (48)			
CE Compliant	Yes			
CSA Certified	Yes			
Mil. Std. Part Number	MS3367-1-9			
UL 62275 Compliant (Type 1, 11)	—			
UL 62275 Compliant (Type 2S, 21S)	Yes			
UL Listed (File #E56854)	Yes			
UL Recognized (File #E56854)	Yes			
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)			
Installation Temperature	-4°F (-20°C) - 32°F (0°C)			
Operating Temperature	-76°F (-60°C) - 185°F (85°C)			
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.			

RoHS Compliancy Status	Compliant
UPC	07498354078
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.2210
Std. Ctn. Qty.	10000
Std. Ctn. Volume (cf)	2.2103
Min. Order Qty.	1,000.0000
