

Search within category

GO

BUY NOW

DESIGN / INSTALL



PLT3I-M3

Pan-Ty® locking tie, intermediate cross section, 11.4" (290mm) length, nylon 6.6, orange.

|                                     |                                                                                                                      |       |           |                    |              |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------|-------|-----------|--------------------|--------------|
| Specs                               | Packaging Details                                                                                                    | Tools | Documents | ★ Add to Favorites | 🛒 Add to BOM |
| Material                            | Nylon 6.6                                                                                                            |       |           |                    |              |
| Application                         | General                                                                                                              |       |           |                    |              |
| Color                               | Orange                                                                                                               |       |           |                    |              |
| Cross Section                       | Intermediate                                                                                                         |       |           |                    |              |
| Locking Style                       | Locking                                                                                                              |       |           |                    |              |
| Min. Loop Tensile Strength Lbs. (N) | 40 (178)                                                                                                             |       |           |                    |              |
| Plenum-Rated                        | Yes, AH-2                                                                                                            |       |           |                    |              |
| Tool                                | GTS-E, GS2B, PTS, PPTS, STS2                                                                                         |       |           |                    |              |
| Length In (mm)                      | 11.4 (290)                                                                                                           |       |           |                    |              |
| Thickness In (mm)                   | 0.052 (1.3)                                                                                                          |       |           |                    |              |
| Bundle Diameter Range In. (mm)      | 0.06 (1.5) - 3.00 (76)                                                                                               |       |           |                    |              |
| CE Compliant                        | Yes                                                                                                                  |       |           |                    |              |
| CSA Certified                       | Yes                                                                                                                  |       |           |                    |              |
| Mil. Std. Part Number               | —                                                                                                                    |       |           |                    |              |
| UL 62275 Compliant (Type 1, 11)     | No                                                                                                                   |       |           |                    |              |
| UL 62275 Compliant (Type 2, 21)     | Yes                                                                                                                  |       |           |                    |              |
| UL Listed (File #E56854)            | Yes                                                                                                                  |       |           |                    |              |
| UL Recognized (File #E56854)        | Yes                                                                                                                  |       |           |                    |              |
| Continuous Use Temperature Range    | -76°F (-60°C) - 185°F (85°C)                                                                                         |       |           |                    |              |
| Environment                         | Plenum                                                                                                               |       |           |                    |              |
| Installation Temperature            | -4°F (-20°C) - 32°F (0°C)                                                                                            |       |           |                    |              |
| Min. Loop Tensile Strength (N)      | 178                                                                                                                  |       |           |                    |              |
| Operating Temperature               | -76°F (-60°C) - 185°F (85°C)                                                                                         |       |           |                    |              |
| Part Features                       | One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength. |       |           |                    |              |
| Width In (mm)                       | 0.145 (3.7)                                                                                                          |       |           |                    |              |
| RoHS Compliancy Status              | Compliant                                                                                                            |       |           |                    |              |
| Min. Order Qty.                     | 1,000.0000                                                                                                           |       |           |                    |              |